YASELAN

Specification sheet

KT-9060-AI

UV flatbed printers



Model	KT-9060-AI
Printheads	Ricoh G5i, 1–6 heads / GH2220, 2–8 heads
Print speed	Mode / Passes / Ricoh G5i / Ricoh GH2220 High resolution mode / 8 passes-pass / 5 m²/h / 9 m²/h Production mode / 6 passes-pass / 7 m²/h / 12 m²/h Sketch mode / 4 passes-pass / 10 m²/h / 16 m²/h
Ink colors	C / M / Y / K / White / Varnish
Print area	900 × 600 mm
Max media thickness	120 mm (40 mm with camera vision positioning)
RIP software	PhotoPrint
File formats	TIFF / JPG / EPS / PDF
Interface	Gigabit Ethernet, USB
Operating system	Windows 7/10, 64-bit (Professional or Ultimate)
Drying	LED-UV curing
Media	Advertising and decoration boards, metal sheet, glass, wood, plastic
Power	3,000 W (including 750 W suction fan)
Operating environment	20–30 °C, 40–70% humidity
Power supply	AC 220 V ±10%, 50 Hz
Net weight	500 kg
Machine dimensions (L × W × H)	2,540 × 1,655 × 1,240 mm
Shipping dimensions (L × W × H)	2,650 × 1,750 × 1,600 mm
AI camera vision positioning	Full-frame camera vision positioning
Computer	Intel i7-10700 or above, 32 GB RAM, 512 GB SSD + 1 TB HDD

Scan to request a quote

yaselanprinters.com